



## UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.		
09/601,886	10/27/2000	Kazuo Tsubouchi	SUGI:091	3777		
759	90 06/02/2004		EXAMINER			
Parkhurst & W	Parkhurst & Wendel			PATEL, AJIT		
Suite 210 1421 Prince Stre	eet		ART UNIT	PAPER NUMBER		
Alexandria, VA 22314-2805			2664	8		
			DATE MAILED: 06/02/2004	1		

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.	Applicant(s)				
	•	09/601,886	TSUBOUCHI ET A	AL.			
	Office Action Summary	Examiner	Art Unit				
		AJIT G. PATEL	2664				
	The MAILING DATE of this communication	n appears on the cover sheet w	vith the correspondence ad	dress			
Period fo	• •						
THE - Exte after - If the - If NO - Failt Any	IORTENED STATUTORY PERIOD FOR R MAILING DATE OF THIS COMMUNICATI ensions of time may be available under the provisions of 37 Cr r SIX (6) MONTHS from the mailing date of this communicative e period for reply specified above is less than thirty (30) days of period for reply is specified above, the maximum statutory pure to reply within the set or extended period for reply will, by reply received by the Office later than three months after the led patent term adjustment. See 37 CFR 1.704(b).	ON. FR 1.136(a). In no event, however, may a con. , a reply within the statutory minimum of this period will apply and will expire SIX (6) MO statute, cause the application to become A	reply be timely filed irty (30) days will be considered timely NTHS from the mailing date of this constant of the constant of				
Status							
1)	Responsive to communication(s) filed on	17 February 2004.		•			
-		This action is non-final.					
· · · · ·	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is						
	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposit	ion of Claims						
4)⊠	Claim(s) 1-26 is/are pending in the applic	ation.					
,	4a) Of the above claim(s) is/are withdrawn from consideration.						
5)⊠	☐ Claim(s) 9-15 is/are allowed.						
6)⊠	∑ Claim(s) <u>1,6-8,16-18 and 23-26</u> is/are rejected.						
7)🖂	☑ Claim(s) <u>2-5,19-22</u> is/are objected to.						
8)[	Claim(s) are subject to restriction a	and/or election requirement.					
Applicat	ion Papers						
9)[	The specification is objected to by the Exa	aminer.					
10)	10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.						
	Applicant may not request that any objection t	to the drawing(s) be held in abeya	ince. See 37 CFR 1.85(a).				
·	Replacement drawing sheet(s) including the c	•	*				
11)	The oath or declaration is objected to by the	he Examiner. Note the attache	d Office Action or form PT	O-152.			
Priority	under 35 U.S.C. § 119		·				
•	Acknowledgment is made of a claim for fo  All b) Some * c) None of:  Certified copies of the priority docu		§ 119(a)-(d) or (f).				
	2. Certified copies of the priority docu		Application No				
	3. Copies of the certified copies of the			Stage			
	application from the International B	ureau (PCT Rule 17.2(a)).		-			
* (	See the attached detailed Office action for	a list of the certified copies no	t received.				
			•				
Attachmer	nt(s)						
	ce of References Cited (PTO-892)	4) Interview	Summary (PTO-413)				
2) D Notic	ce of Draftsperson's Patent Drawing Review (PTO-94	Paper No	(s)/Mail Date				
	mation Disclosure Statement(s) (PTO-1449 or PTO/Ser No(s)/Mail Date	SB/08) 5)  Notice of 6)  Other:	Informal Patent Application (PTC	)-152)			

Art Unit: 2664

- 1. The following is a quotation of the appropriate paragraphs of 35 U. S.C. 102 that form the basis for the rejections under this section made in this Office action:

  (e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351 (a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.
- 2. Claims 1, 6-8, 16-18 and 23-26 are rejected under 35 U.S.C. 102(e)(2) as being anticipated by Tsubouchi et al. (U.S. Pat. 6,061,342), hereinafter referred to as Tsubouchi.

In regard to claim 1, Tsubouchi discloses a code division multiple access communication system in which in a transmitter (Fig. 2 and transmission apparatus, column 2 and line 57), a code division multiple signal (Fig. 3A), composed of a data division (Data Packet part of Fig. 3A) obtained by multiplying (multiplying, column 3, line 52) a baseband data (baseband data, column 3, line 21) and an orthogonal code (orthogonal PN code, column 3, lines 42-43) and a preamble division (combination of synchronization packet and dummy data in Fig. 3A) including synchronization code sequences (synchronization packet in Fig. 3A) to attain the chip synchronization (bit

Art Unit: 2664

synchronization, column 4, line 42) of the orthogonal code in a receiver (Fig. 1 and receiving apparatus, column 2 and line 54), is modulated (see function described in column 3, lines 56-58) with a carrier (carrier, column 3, line 56) having a given center frequency (carry frequency, column 5, line 13) and transmitted, and in the receiver, a correlation peak (correlation peak, column 4, lines 52-53) is detected (detected, column 4, line 53) from among the synchronization code sequences (synchronization packet) in the preamble division by a surface acoustic wave matched filter (SAW, column 4, line 53) and the baseband data (baseband data, column 5, line 23) in the data division is demodulated (demodulated, column 5, line 22) by the orthogonal code (orthogonal PN code, column 5, lines 21-22) generated on the detection timing (timing, column 4, line 41), wherein the preamble division has plural synchronization code sequences (11-bit Barker code, column 3, line 36), and the surface acoustic wave matched filter (SAW) detects the correlation peak of at least one (see envelope detection circuit 15, column 4, lines 45-47) from among the plural synchronization code sequences and generates the orthogonal code on the detection timing (Fig. 5B) of the correlation peak. In regard to claims 6-7 and 23-24, the feature that the chip rate of the synchronization code sequence in the preamble division is higher than, or not less than two as high as, the chip rate of the orthogonal code in the data division is already well known in the prior arts that are conformed to the industrial standards such as IS-95. The commonly used 11-chip Barker code and 64-chip orthogonal PN code packet is a trivial example. The main reason to set the ratio of the synchronization code sequence to the chip rate

Art Unit: 2664

of the orthogonal code to an integral number is obviously just for designing and fabricating the circuits much easier.

In regard to claims 8 and 25, the subject matter 64 chips for the chip length of the orthogonal code in the data division is already well known in the prior art such as IS-95 CDMA standard.

In regard to claim 16, Tsubouchi discloses a code division multiple access ommunication system in which in a transmitter (Fig. 2 and transmission apparatus, column 2 and line 57), a code division multiple signal (Fig. 3A), composed of a data division (Data Packet part of Fig. 3A) obtained by multiplying (multiplying, column 3, line 52) a baseband data (baseband data, column 3, line 21) and an orthogonal code (orthogonal PN code, column 3, lines 42-43) and a preamble division (combination of synchronization packet and dummy data in Fig. 3A) including synchronization code sequences (synchronization packet in Fig. 3A) to attain the chip synchronization (bit synchronization, column 4, line 42) of the orthogonal code in a receiver (Fig. 1 and receiving apparatus, column 2 and line 54), is modulated (see function described in column 3, lines 56-58) with a carrier (carrier, column 3, line 56) having a given center frequency (carry frequency, column 5, line 13) and transmitted, and in the receiver, a correlation peak (correlation peak, column 4, lines 52-53) is detected (detected, column 4, line 53) from among the synchronization code sequences (synchronization packet) in the preamble division by a surface acoustic wave matched filter (SAW, column 4, line 53) and the baseband data (baseband data, column 5, line 23) in the data division is demodulated (demodulated, column 5, line 22) by the orthogonal code (orthogonal PN

Art Unit: 2664

Page 5

code, column 5, lines 21-22) generated on the detection timing (timing, column 4, line 41), wherein in the receiver, the orthogonal code (orthogonal PN code) which is generated on the detection timing (timing) of the correlation peak (correlation peak) in the surface acoustic wave matched filter (SAW) is multiplied (Multiplier, column 5, linel7) by the received code division multiple signal (signal, column 5, line 18) to generate a narrow-band modulation signal (output of Multiplier 22, column 5, linel9) and the generated narrow-band modulation signal is demodulated (demodulated, column 5, line 22) by a carrier (carrier, column 5, line 14) generated from a local oscillator (Carrier Generator 23, column 5, line 15) provided in the receiver to reproduce the original baseband data (original baseband data, column 5, line 23).

In regard to claims 17 and 18, Tsubouchi discloses a local oscillator (Carrier Generator 23) provided in the receiver generates the carrier (carrier) having the frequency equal to (inphase) or different (out of phase, i.e. 90°, 180° or 270°) center frequency (in-phase carrier) or of the carrier generated in the transmitter (transmission apparatus), and the generated carrier (carrier, column 5, line 14) from the local oscillator is multiplied (Multiplier, column 5, line 17) by the narrow-band modulation signal (output of Multiplier 22, column 5, line 19) to demodulate to the original baseband data (original baseband data).

In regard to claim 26, Tsubouchi discloses the surface acoustic wave matched filter has an aluminum nitride film (aluminum nitride film, column 4, line 9) as its component.

3. Claims 9-15 are allowable.

Art Unit: 2664

- 4. Claims 2-5 and 19-22 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.
- 5. Applicant's arguments filed 2/17/04 have been fully considered but they are not persuasive. Applicant argued that the Tsubouchi fails to disclose a plurality of synchronized code sequences to be incorporated in the code division multiple access signal. However, in fig. 3A Tsubouchi disclose a synchronized code sequence incorporated in a header part of the packet. It is noted that the user transmits plurality of packets one after another until it finishes the transmission. Therefore, each packet comprising header having the synchronized code sequence included in a code division multiple access signal. In other word, the code division multiple signal incorporates a plurality of packets, each having a header part includes the synchronized code sequence.
- 6. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any

Art Unit: 2664

extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to AJIT G. PATEL whose telephone number is 703-308-5347. The examiner can normally be reached on MONDAY-THURSDAY.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Wellington Chin can be reached on 703-305-4366. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

AP

California :